

IN THE CLAIMS

Presented below is a complete set of claims with current status indicators.

1. (previously amended) An implantable medical electrical lead for transmitting electrical signals between an implantable medical device and cardiac tissue and configured to significantly attenuate far-field and repolarization signals, the lead comprising:

a lead body defining a proximal end comprising a connector assembly configured for connection to the implantable medical device, the lead body further defining a distal region; and

a helical tip electrode extending from the distal region and a second electrode spaced proximally from the tip electrode, the second electrode having a surface area in the range of 14 to 40 mm², the helical tip electrode having an active surface area in the range of 3.0 to 10 mm² and the spacing between the second electrode and the helical tip electrode being in the range of 1.0 mm to about 3.5 mm.

2. (canceled).

3. (previously amended) The lead of claim 1 wherein the helical tip electrode is extendable and retractable relative to the distal region of the lead.

4. (original) The lead of claim 1 wherein the second electrode comprises a ring electrode.

5. (canceled).

6. (previously amended) The lead of claim 1 wherein the helical tip electrode comprises a distal portion and a proximal portion, the distal portion comprising the electrically active portion of the tip electrode, and the proximal portion of the tip electrode being electrically insulating.

7. (original) The lead of claim 1 further comprising:
a steroid disposed on the distal region of the lead.

8. (original) The lead of claim 1 further comprising:
a cardioverting-defibrillating electrode disposed on the distal end of the lead
proximal to the second electrode.

9. (original) The lead of claim 8 wherein the cardioverting-defibrillating
electrode is spaced from a distal extremity of the lead by a distance in the range of
between about 5 and about 20 mm.

10. (original) The lead of claim 1, wherein the lead body is configured for
placement in the right atrium.

11. (original) The lead of claim 1, wherein the lead body is configured for
placement in at least one of a ventricle and a coronary sinus.

12. (canceled).

13. (previously amended) An implantable medical electrical lead for
transmitting electrical signals between an implantable medical device and cardiac tissue
and configured to significantly attenuate far-field and repolarization signals, the lead
comprising:

a lead body defining a proximal end comprising a connector assembly configured
for connection to the implantable medical device, the lead body further defining a distal
region;

a helical tip electrode extending from the distal region, and a second electrode
spaced proximally from the helical tip electrode and connected to the lead body, the
second electrode having a surface area in the range of 10 to 40 mm², the helical tip
electrode having an active surface area in the range of 3.0 to 10 mm² and the spacing

between the second electrode and the helical tip electrode being in the range of 1.0 mm to about 3.5 mm.

14. (previously amended) The lead of claim 13 wherein the helical tip electrode is extendable from the distal end of the lead.

15. (original) The lead of claim 14 wherein the helical tip electrode comprises a distal portion and a proximal portion, the distal portion comprising an electrically active portion of the tip electrode, and the proximal portion of the tip electrode being electrically insulating.

16. (original) The lead of claim 13 further comprising:
a steroid disposed on the distal end of the lead distal to the second electrode.

17. (original) The lead of claim 13 further comprising:
a cardioverting-defibrillating electrode disposed on the distal end of the lead proximal to the second electrode.

18. (previously amended) An implantable medical electrical lead for transmitting electrical signals between an implantable medical device and cardiac tissue and configured to significantly attenuate far-field and repolarization signals, the lead comprising:

a lead body defining a proximal end comprising a connector assembly configured for connection to the implantable medical device, the lead body further defining a distal region;

a helical tip electrode extending from the distal region, and a second electrode spaced proximally from the helical tip electrode and connected to the lead body, the second electrode having a surface area in the range of 14 to 40 mm², the helical tip electrode having an active surface area in the range of 3.0 to 10 mm² and the spacing between the second electrode and the helical tip electrode being in the range of 1.0 mm to about 3.5 mm.

19. (original) The lead of claim 18 wherein the helical tip electrode is extendable and retractable relative to the distal region of the lead.

20. (original) The lead of claim 18 wherein the helical tip electrode comprises a distal portion and a proximal portion, the distal portion comprising the electrically active portion of the tip electrode, and the proximal portion of the tip electrode being electrically insulating.

21. (original) The lead of claim 18 further comprising:
a steroid disposed on the distal region of the lead.

22. (original) The lead of claim 18, wherein the lead body is configured for placement in the right atrium.

23. (original) The lead of claim 18, wherein the lead body is configured for placement in at least one of a ventricle and a coronary sinus.